

Description

Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS51993M506L
Minimum Qty (MOQ):	1 EA
NSN:	5325-01-115-6854
Schedule B:	7318.16.0060
ECCN:	9A991
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS51993M506L Specifications

Thread Class:	3b
Length:	0.730 Inches Minimum And 0.770 Inches Maximum
Insert Size:	5/8-18 Uns,0.5894 In. Min,0.5914 In. Max Pitch Dia
Features Provided:	Individually Keyed
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Special Features:	Furnished With Lock Ring
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Style Designator:	Serrated
Thread Series Designator:	Unjf

How to Order

Order this insert solid from our inventory online by visiting <https://military-fasteners.com/inserts/screw+thread+inserts/MS51993M506L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.