

Description

MS90335-6 Electrical Receptacle Connector

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS903356
Minimum Qty (MOQ):	1
NSN:	5935-01-064-9178
ECCN:	EAR99
National Motor Freight:	061680, Elec Wiring Plugs Etc



NO IMAGE
AVAILABLE

P/N MS90335-6 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Body Style:	Thru-hole Mount
Overall Length:	0.875 Inches Maximum
Overall Diameter:	0.531 Inches Nominal
Environmental Protection:	Moisture Resistant
Distance From Mounting Shoulder To Rear Face:	0.847 Inches Nominal
Mounting Facility Thickness:	0.100 Inches Maximum
Threaded Device Type:	Mounting Bushing
Mating End Quantity:	1
Contact Position Arrangement Style:	Nonstd Single Mating End
Contact Removability:	Nonremovable Single Mating End Single Contact Grouping
Polarization Method:	Keyway Or Multiple Keyway
Insert Position In Deg:	0.0
Shell Type:	Solid
Connector Locking Method:	Spring Friction
End Item Identification:	Aircraft Stratolifer C-135
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.437 Inches
Terminal Location:	Side Single Mating End Single Contact Grouping
Contact Material:	Copper Alloy Single Mating End Single Contact Grouping
Contact Surface Treatment:	Gold Single Mating End Single Contact Grouping And Copper Single Mating End Single Contact Grouping
Insert Material:	Plastic Polytetrafluoroethylene Single Mating End
Contact Surface Treatment Document And Classification:	Mil-c-14550 Mil Spec 1st Treatment Response Single Mating End Single Contact Grouping And Mil-g-45204,ty 2,cl 0,grade C Mil Spec 2nd Treatment Response Single Mating End Single Contact Grouping
Terminal Type:	Screw Single Mating End Single Contact Grouping
Contact Material Document And Classification:	Qq-c-530,heat Treated Mil-h-7199 Fed Spec Single Material Response Single Mating End Single Contact Grouping
Shell Material:	Copper Alloy
Shell Surface Treatment:	Nickel

Shell Surface Treatment Document And Classification:	Qq-n-290,class 1,grade F Fed Spec Single Treatment Response
Shell Material Document And Classification:	Qq-b-626,hal Hard Fed Spec Single Material Response
Insert Material Document And Classification:	Mil-p-19468 Mil Spec Single Material Response Single Mating End
Included Contact Quantity:	1 Single Mating End Single Contact Grouping
Bushing Accommodation Hole Shape:	Round
Included Contact Type:	Round Socket Single Mating End Single Contact Grouping
Precious Material And Location:	Contact Surface Gold
Precious Material And Weight:	0.005 Gold Grains, Troy
Precious Material:	Gold
Test Data Document:	81349-mil-p-7788 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Thread Series Designator:	Un
Specification/standard Data:	96906-ms90335 Government Standard

How to Order

Order this electrical receptacle connector from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+receptacle+connectors/MS90335-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.