

Description

Fastener Length: 1-1/64", Thread: 1/4-28, Thread Length: 3/4", fine thread, hole in head, MS9034 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS903414
Minimum Qty (MOQ):	10
NSN:	5306-00-576-0010
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9034-14 Specifications

Thread Class:	1a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.810 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.330 Inches Nominal
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.438 Inches Nominal
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.190 Inches Minimum And 0.250 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5732 Assn Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9034-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.