

Description

Fastener Length: 1-3/8", Thread: 1/4-28, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS903420
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-224-0441
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS9034-20 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.750 Inches Minimum And 0.810 Inches Maximum
<b>Fastener Length:</b>	1.375 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.330 Inches Nominal
<b>Width Between Flats:</b>	0.304 Inches Minimum And 0.313 Inches Maximum
<b>Extended Washer Diameter:</b>	0.438 Inches Nominal
<b>Extended Washer Thickness:</b>	0.060 Inches Minimum And 0.070 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.565 Inches Minimum And 0.625 Inches Maximum
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
<b>Minimum Yield Strength:</b>	85000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	63.0 Microinches Grip
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt12 from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9034-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.