

Description

Fastener Length: 3-1/8", Thread: 1/4-28, Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS903437
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-225-6708
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9034-37 Specifications

Thread Class:	1a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum
Fastener Length:	3.125 Inches Nominal
Head Style:	Double Hexagon W/hole
Head Height:	0.330 Inches Nominal
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.500 Inches Nominal
Extended Washer Thickness:	0.057 Inches Minimum And 0.063 Inches Maximum
First Diameter From Head:	0.218 Inches Minimum And 0.228 Inches Maximum
Second Diameter From Head:	0.240 Inches Minimum And 0.247 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	2.375 Inches Nominal
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:	3.125 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Yield Strength:	85000 Pounds Per Square Inch
Externally Relieved Body Diameter Quantity:	2
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9034-37> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.