

**Description**

Fastener Length: 3-1/8", Thread: 1/4-28, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS903437
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-225-6708
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS9034-37 Specifications

<b>Thread Class:</b>	1a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.750 Inches Minimum
<b>Fastener Length:</b>	3.125 Inches Nominal
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.330 Inches Nominal
<b>Width Between Flats:</b>	0.304 Inches Minimum And 0.313 Inches Maximum
<b>Extended Washer Diameter:</b>	0.500 Inches Nominal
<b>Extended Washer Thickness:</b>	0.057 Inches Minimum And 0.063 Inches Maximum
<b>First Diameter From Head:</b>	0.218 Inches Minimum And 0.228 Inches Maximum
<b>Second Diameter From Head:</b>	0.240 Inches Minimum And 0.247 Inches Maximum
<b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b>	2.375 Inches Nominal
<b>Distance From Largest Bearing Surface Of Head To End Of Second Diameter:</b>	3.125 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Yield Strength:</b>	85000 Pounds Per Square Inch
<b>Externally Relieved Body Diameter Quantity:</b>	2
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5735 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9034-37> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.