

P/N MS90353-0503

Description

Fastener Length: 1/2

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS903530503

Minimum Qty (MOQ): 10

NSN: 5320-00-866-4982

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N MS90353-0503 Specifications

Fastener Length: 0.466 Inches Maximum Head Style: Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) Shank Diameter: 0.466 Inches Maximum O.162 Inches Minimum And 0.164 Inches Maximum	
Charle Biometers	
Shank Diameter: 0.102 inches Minimum And 0.104 inches Maximum	
Shank Style: Self-plugging Mechanically Locked Stem	
Head Major Diameter: 0.333 Inches Maximum	
Expansion Device: Serrated Stem-type W	
Grip Length: 0.156 Inches Minimum And 0.220 Inches Maximum	
Hardness Rating: 32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body	
Hardness Rating: 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem	
Shear Strength: 2340 Single Pounds Per Square Inch	
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum	
Special Features: Mechanical Lock Steel Aisi 660, steel Qq-s-633 Comp C1144	
Material: Steel Comp 1144 Sleeve	
Material: Steel Comp 4037 Body Or Steel Comp 4130 Body	
Material: Steel Comp 8740 Stem	
Material Document And Classification: Mil-s-6049 Mil Spec Single Material Response Stem Or Qq-w-405 Fed Spec Single Material Response	se Stem
Material Document And Classification: Qq-s-633 Fed Spec Single Material Response Sleeve	
Material Document And Classification: Qq-w-405 Fed Spec 1st Material Response Body Or Qq-w-405 Fed Spec 2nd Material Response Body Spec 2nd Material Response Body	dy Or Mil-s-6758 Mil
Surface Treatment: Cadmium Body	
Surface Treatment: Cadmium Mechanical Lock	
Surface Treatment: Cadmium Stem	
Surface Treatment Document And Classification: Qq-p-416,ty 1 Or 2,cl 3 Fed Spec Single Treatment Response Stem	
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body	
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl3 Fed Spec Single Treatment Response Mechanical Lock	

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/MS90353-0503 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/MS90353-0503 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/MS90353-0503 and selecting the quantity you want then