

## P/N MS90353-0602

### **Description**

Fastener Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS903530602

Minimum Qty (MOQ): 20 EA

NSN: 5320-00-866-4659

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS90353-0602 Specifications

Fastener Length:	0.475 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.386 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.094 Inches Minimum And 0.157 Inches Maximum
Hardness Rating:	32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Shear Strength:	3450 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Mechanical Lock Steel Aisi 660,steel Qq-s-633 C1144
Material:	Steel Comp 1144 Sleeve
Material:	Steel Comp 4037 Body Or Steel Comp 4130 Body
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Stem Or Qq-w-405 Fed Spec Single Material Response Stem
Material Document And Classification:	Qq-s-633 Fed Spec Single Material Response Sleeve
Material Document And Classification:	Qq-w-405 Fed Spec 1st Material Response Body Or Qq-w-405 Fed Spec 2nd Material Response Body Or Mil-s-6758 Mil Spec 2nd Material Response Body
Surface Treatment:	Cadmium Body
Surface Treatment:	Cadmium Mechanical Lock
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1 Or 2,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl3 Fed Spec Single Treatment Response Mechanical Lock

## **How to Order**

