

P/N MS90353-0605

Description

Fastener Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS903530605

Minimum Qty (MOQ):

NSN: 5320-00-866-4661

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N MS90353-0605 Specifications

0.636 Inches Maximum
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.197 Inches Minimum And 0.199 Inches Maximum
0.386 Inches Maximum
Serrated Stem-type W
0.281 Inches Minimum And 0.345 Inches Maximum
32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body
48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
3450 Single Pounds Per Square Inch
99.0 Degrees Minimum And 101.0 Degrees Maximum
Mechanical Lock Steel Aisi 660,steel Qq-s-633 C1144
Steel Comp 1144 Sleeve
Steel Comp 4037 Body Or Steel Comp 4130 Body
Steel Comp 8740 Stem
Mil-s-6049 Mil Spec Single Material Response Stem Or Qq-w-405 Fed Spec Single Material Response Stem
Qq-s-633 Fed Spec Single Material Response Sleeve
Qq-w-405 Fed Spec 1st Material Response Body Or Qq-w-405 Fed Spec 2nd Material Response Body Or Mil-s-6758 Mil Spec 2nd Material Response Body
Cadmium Body
Cadmium Mechanical Lock
Cadmium Stem
Qq-p-416,ty 1 Or 2,cl 3 Fed Spec Single Treatment Response Stem
Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body
Qq-p-416,ty 2,cl3 Fed Spec Single Treatment Response Mechanical Lock

How to Order

