

P/N MS90353-0613

Military-Fasteners.com

Description

Fastener Length: 1-1/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS903530613
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-731-9980
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS90353-0613 Specifications

Fastener Length:	1.136 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.188 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.386 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.781 Inches Minimum And 0.845 Inches Maximum
Hardness Rating:	32.0 Rockwell C Minimum Sleeve And 40.0 Rockwell C Maximum Sleeve
Hardness Rating:	48.0 Rockwell C Minimum Bolt And 53.0 Rockwell C Maximum Bolt
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve
Material:	Steel Comp 8740 Bolt
Material:	Steel Mechanical Lock
Material Document And Classification:	Aisi Assn Std All Material Responses Sleeve
Material Document And Classification:	Aisi Assn Std Single Material Response Bolt
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Mechanical Lock
Surface Treatment:	Cadmium Bolt Or Cadmium Bolt And Chromate Bolt
Surface Treatment Document And Classification:	Qq-p-416 Ty 1 Fed Spec 1st Treatment Response Bolt Or Qq-p-416 Ty 2 Cl 3 Fed Spec 2nd Treatment Response Bolt
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Fed Spec Single Treatment Response Mechanical Lock

How to Order

Order this fastener from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/MS90353-0613</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.