

Description

Fastener Length: 1-3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS903530614
Minimum Qty (MOQ):	10
NSN:	5320-00-753-7301
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS90353-0614 Specifications

Fastener Length:	1.199 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.188 Inches Nominal
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.386 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.844 Inches Minimum And 0.907 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve
Material:	Steel Comp 8740 Bolt
Material:	Steel Mechanical Lock
Surface Treatment:	Cadmium Bolt
Surface Treatment:	Cadmium Mechanical Lock
Surface Treatment:	Cadmium Sleeve
Surface Treatment Document And Classification:	Mil-f-81172 Mil Spec Single Treatment Response Bolt
Surface Treatment Document And Classification:	Mil-f-81177 Mil Spec Single Treatment Response Mechanical Lock
Surface Treatment Document And Classification:	Mil-f-81177 Mil Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353-0614> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.