

**Description**

Fastener Length: 1-3/16

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS903530614
Minimum Qty (MOQ):	10
NSN:	5320-00-753-7301
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS90353-0614 Specifications

<b>Fastener Length:</b>	1.199 Inches Nominal
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.188 Inches Nominal
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.386 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.844 Inches Minimum And 0.907 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve
<b>Material:</b>	Steel Comp 8740 Bolt
<b>Material:</b>	Steel Mechanical Lock
<b>Surface Treatment:</b>	Cadmium Bolt
<b>Surface Treatment:</b>	Cadmium Mechanical Lock
<b>Surface Treatment:</b>	Cadmium Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-f-81172 Mil Spec Single Treatment Response Bolt
<b>Surface Treatment Document And Classification:</b>	Mil-f-81177 Mil Spec Single Treatment Response Mechanical Lock
<b>Surface Treatment Document And Classification:</b>	Mil-f-81177 Mil Spec Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353-0614> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.