

P/N MS90353-0616

Description

Fastener Length: 1-1/8

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS903530616

Minimum Qty (MOQ): 5

NSN: 5320-00-181-5991

Schedule B: 7318.15.2010

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N MS90353-0616 Specifications

1.163 Inches Minimum And 1.193 Inches Maximum
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.197 Inches Minimum And 0.199 Inches Maximum
Self-plugging Mechanically Locked Stem
0.386 Inches Maximum
Serrated Stem-type W
0.969 Inches Minimum And 1.032 Inches Maximum
48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
3450 Single Pounds Per Square Inch
99.0 Degrees Minimum And 101.0 Degrees Maximum
Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
Steel Comp 8740 Expander
66 Fed Std 1st Material Response Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or 66 Fed Std 3rd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve
Mil-s-6049 Mil Spec Single Material Response Stem Or Astm A547 Assn Std Single Material Response Stem
Cadmium Sleeve And Chromate Sleeve
Cadmium Stem
Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/MS90353-0616 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/MS90353-0616 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/MS90353-0616 and selecting the quantity you want then