

Description

Fastener Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS903530617
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-181-5996
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

P/N MS90353-0617 Specifications

Fastener Length:	1.225 Inches Minimum And 1.255 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Head Major Diameter:	0.386 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	1.031 Inches Minimum And 1.095 Inches Maximum
Hardness Rating:	32.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Shear Strength:	3450 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4037 Body Or Steel Comp 4130 Body Or Steel Comp 4027 Body Or Steel Comp 8740 Body
Material:	Steel Comp 4037 Stem Or Steel Comp 4130 Stem Or Steel Comp 4027 Stem Or Steel Comp 8740 Stem
Material Document And Classification:	66 Fed Std All Material Responses Body Or Mil-s-6050 Mil Spec 1st Material Response Body
Material Document And Classification:	66 Fed Std All Material Responses Stem Or Mil-s-6050 Mil Spec 1st Material Response Stem
Surface Treatment:	Cadmium Body
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Body

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353-0617> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.