

P/N MS90353-0803

Military-Fasteners.com

#### Description

Fastener Length: 37/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | MS903530803                                 |
|-------------------------|---|
| Minimum Qty (MOQ):      | 5 EA  |
| NSN:                    | 5320-00-866-4669                            |
| Schedule B:             | 7318.15.2010                                |
| ECCN:                   | 9A991                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



# P/N MS90353-0803 Specifications

| Fastener Length:                                  | 0.586 Inches Maximum  |
|---|---|
| -   |   |
| Head Style:                                       | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)  |
| Shank Diameter:                                   | 0.258 Inches Minimum And 0.260 Inches Maximum   |
| Shank Style:                                      | Self-plugging Mechanically Locked Stem  |
| Head Major Diameter:                              | 0.507 Inches Maximum  |
| Expansion Device:                                 | Serrated Stem-type W  |
| Grip Length:                                      | 0.156 Inches Minimum And 0.220 Inches Maximum   |
| Hardness Rating:                                  | 32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body   |
| Hardness Rating:                                  | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem   |
| Shear Strength:                                   | 5900 Single Pounds Per Square Inch  |
| Countersink Angle:                                | 99.0 Degrees Minimum And 101.0 Degrees Maximum  |
| Special Features:                                 | Mechanical Lock Steel Aisi 660,steel Qq-s-633 Comp C1144  |
| Material:   | Steel Comp 1144 Sleeve  |
| Material:   | Steel Comp 4037 Body Or Steel Comp 4130 Body  |
| Material:   | Steel Comp 8740 Stem  |
| Material Document And Classification:             | Mil-s-6049 Mil Spec Single Material Response Stem Or Qq-w-405 Fed Spec Single Material Response Stem  |
| Material Document And Classification:             | Qq-s-633 Fed Spec Single Material Response Sleeve   |
| Material Document And Classification:             | Qq-w-405 Fed Spec 1st Material Response Body Or Qq-w-405 Fed Spec 2nd Material Response Body Or Mil-s-6758 Mil Spec 2nd<br>Material Response Body |
| Surface Treatment:                                | Cadmium Body  |
| Surface Treatment:                                | Cadmium Mechanical Lock   |
| Surface Treatment:                                | Cadmium Stem  |
| Surface Treatment Document And<br>Classification: | Qq-p-416,ty 1 Or 2,cl 3 Fed Spec Single Treatment Response Stem   |
| Surface Treatment Document And<br>Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body  |
| Surface Treatment Document And<br>Classification: | Qq-p-416,ty 2,cl3 Fed Spec Single Treatment Response Mechanical Lock  |

## How to Order

Order this fastener from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/MS90353-0803</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.