

## P/N MS90353-0807

## **Description**

Fastener Length: 13/16"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS903530807

Minimum Qty (MOQ): 15 EA

NSN: 5320-00-813-6313

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS90353-0807 Specifications

| Fastener Length:                               | 0.836 Inches Maximum   |
|--|--|
| Head Style:                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)   |
| Shank Diameter:                                | 0.258 Inches Minimum And 0.260 Inches Maximum  |
| Shank Style:                                   | Self-plugging Mechanically Locked Stem   |
| Head Major Diameter:                           | 0.507 Inches Maximum   |
| Expansion Device:                              | Serrated Stem-type W   |
| Grip Length:                                   | 0.406 Inches Minimum And 0.470 Inches Maximum  |
| Hardness Rating:                               | 32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body  |
| Hardness Rating:                               | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem  |
| Shear Strength:                                | 5900 Single Pounds Per Square Inch   |
| Countersink Angle:                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum   |
| Special Features:                              | Mechanical Lock Steel Aisi 660; Mechanical Lock Steel,qq-s-633 Comp C1144  |
| Material:                                      | Steel Comp 1144 Sleeve   |
| Material:                                      | Steel Comp 4037 Body Or Steel Comp 4130 Body   |
| Material:                                      | Steel Comp 8740 Stem   |
| Material Document And Classification:          | Mil-s-6049 Mil Spec Single Material Response Stem Or Qq-w-405 Fed Spec Single Material Response Stem   |
| Material Document And Classification:          | Qq-s-633 Fed Spec Single Material Response Sleeve  |
| Material Document And Classification:          | Qq-w-405 Fed Spec 1st Material Response Body Or Qq-w-405 Fed Spec 2nd Material Response Body Or Mil-s-6758 Mil Spec 2nd Material Response Body |
| Surface Treatment:                             | Cadmium Body   |
| Surface Treatment:                             | Cadmium Mechanical Lock  |
| Surface Treatment:                             | Cadmium Stem   |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1 Or 2,cl 3 Fed Spec Single Treatment Response Stem  |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body   |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl3 Fed Spec Single Treatment Response Mechanical Lock   |

## **How to Order**

