

P/N MS90353-0810

Description

MS90353 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS903530810

Minimum Qty (MOQ): 10

NSN: 5320-01-548-9271

Schedule B: 7318.15.8085

ECCN: 9A991









^{*} See page 2 for technical characteristics

P/N MS90353-0810 Specifications

Fastener Length:	0.844 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.507 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.844 Inches Nominal
Minimum Tensile Strength:	3650 Pounds Per Square Inch
Hardness Rating:	326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Shear Strength:	5900 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1010 Mechanical Lock Or Steel Comp 1020 Mechanical Lock
Material:	Steel Sleeve
Material:	Steel Stem
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Mechanical Lock Or Ams 5690 Assn Std Single Material Response Mechanical Lock
Material Document And Classification:	Astm A331 Assn Std Single Material Response Stem
Material Document And Classification:	Astm A331 Assn Std Single Material Response Sleeve
Surface Treatment:	Cadmium Mechanical Lock
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416, Type I, Class 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Mechanical Lock
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Sleeve

How to Order

