

Description

Fastener Length: 1-3/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS903531015
Minimum Qty (MOQ):	1 EA
NSN:	5320-00-099-8857
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90353-1015 Specifications

Fastener Length:	1.193 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.310 Inches Minimum And 0.312 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.634 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.906 Inches Minimum And 0.970 Inches Maximum
Hardness Rating:	32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1010 Mechanical Lock Or Steel Comp 1020 Mechanical Lock Or Steel Comp 1144 Mechanical Lock Or Steel Comp 4037 Mechanical Lock Or Steel Comp 4130 Mechanical Lock Or Iron Alloy 660 Mechanical Lock
Material:	Steel Comp 4027 Body Or Steel Comp 4037 Body Or Steel Comp 4130 Body
Material:	Steel Comp 8740 Stem
Material Document And Classification:	66 Fed Std 1st Material Response Body Or Astm A547 Assn Std 2nd Material Response Body Or Mil-s-6758 Mil Spec 3rd Material Response Body
Material Document And Classification:	66 Fed Std 1st Material Response Mechanical Lock Or 66 Fed Std 2nd Material Response Mechanical Lock Or 66 Fed Std 3rd Material Response Mechanical Lock Or 66 Fed Std 4th Material Response Mechanical Lock Or 66 Fed Std 5th Material Response Mechanical Lock Or Ams 5737 Assn Std 6th Material Response Mechanical Lock
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Stem Or Astm A547 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Body And Chromate Body
Surface Treatment:	Cadmium Mechanical Lock Or Passivate Mechanical Lock
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Mechanical Lock Or Qq-p-35 Fed Spec 2nd Treatment Response Mechanical Lock
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Body

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353-1015> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.