

Description

Fastener Length: 1-25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS903531018
Minimum Qty (MOQ):	1 EA
NSN:	5320-00-234-7934
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS90353-1018 Specifications

Fastener Length:	1.366 Inches Minimum And 1.396 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.310 Inches Minimum And 0.312 Inches Maximum
Head Major Diameter:	0.634 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	1.094 Inches Minimum And 1.157 Inches Maximum
Hardness Rating:	32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Shear Strength:	8500 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4037 Body Or Steel Comp 4130 Body
Material:	Steel Comp 8740 Stem
Material Document And Classification:	Qq-w-405 Fed Spec 1st Material Response Body Or Qq-w-405 Fed Spec 2nd Material Response Body Or Mil-c-6758 Mil Spec 2nd Material Response Body
Material Document And Classification:	Qq-w-405 Fed Spec Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem
Surface Treatment:	Cadmium Body
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1 Or 2,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353-1018> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.