

**Description**

blind rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                             |
|-------------------------|---------------------------------------------|
| SKU / Model:            | MS90353S0504                                |
| Minimum Qty (MOQ):      | 10                                          |
| NSN:                    | 5320-00-160-2213                            |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

# P/N MS90353S0504 Specifications

|                                                       |                                                                                                                                                 |
|-------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Fastener Length:</b>                               | 0.405 Inches Maximum                                                                                                                            |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)                                                                  |
| <b>Shank Diameter:</b>                                | 0.162 Inches Minimum And 0.164 Inches Maximum                                                                                                   |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem                                                                                                          |
| <b>Head Major Diameter:</b>                           | 0.333 Inches Maximum                                                                                                                            |
| <b>Expansion Device:</b>                              | Serrated Stem-type W                                                                                                                            |
| <b>Grip Length:</b>                                   | 0.219 Inches Minimum And 0.282 Inches Maximum                                                                                                   |
| <b>Minimum Tensile Strength:</b>                      | 112000 Pounds Per Square Inch                                                                                                                   |
| <b>Hardness Rating:</b>                               | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem                                                                                   |
| <b>Hardness Rating:</b>                               | 48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem                                                                                        |
| <b>Shear Strength:</b>                                | 2340 Single Pounds Per Square Inch                                                                                                              |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                                                                                  |
| <b>Material:</b>                                      | Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve                                                                      |
| <b>Material:</b>                                      | Steel Comp 8740 Stem                                                                                                                            |
| <b>Material:</b>                                      | Steel Comp 4027 Or Steel Comp 4037 Or Steel Comp 4130 Sleeve                                                                                    |
| <b>Material Document And Classification:</b>          | 66 Fed Std All Material Responses Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve |
| <b>Material Document And Classification:</b>          | Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem                                           |
| <b>Material Document And Classification:</b>          | 66 Fed Std All Material Responses Or Astm A547 Assn Std 2nd Material Response Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve               |
| <b>Material Document And Classification:</b>          | Astm A547 Assn Std Single Material Response Or Mil-s-6049 Mil Spec Single Material Response Stem                                                |
| <b>Surface Treatment:</b>                             | Cadmium Sleeve And Chromate Sleeve                                                                                                              |
| <b>Surface Treatment:</b>                             | Cadmium Stem                                                                                                                                    |
| <b>Surface Treatment:</b>                             | Cadmium And Chromate Sleeve                                                                                                                     |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem                                                                                      |
| <b>Surface Treatment Document And Classification:</b> | Qqq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve                                                                                   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353S0504> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.