

Description

Fastener Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90353S0505D
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-467-9296
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90353S0505D Specifications

Fastener Length:	0.622 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.333 Inches Nominal
Expansion Device:	Serrated Stem-type W
End Item Identification:	Aircraft,f16
Grip Length:	0.281 Inches Minimum And 0.345 Inches Maximum
Hardness Rating:	326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Fastener,blind,high Strength, Pull Type,positive Mechanical Lock,100 Degree Flush Head
Special Features:	Installed With Single Action Tool
Material:	Steel Corrosion Resisting Mechanical Lock Or Steel Comp 1010 Mechanical Lock Or Steel Comp 1020 Mechanical Lock Or Steel Comp 1144 Mechanical Lock Or Steel Comp 4037 Mechanical Lock Or Steel Comp 4130 Mechanical Lock Or Iron Alloy 660 Mechanical Lock
Material:	Steel Corrosion Resisting Sleeve
Material:	Steel Corrosion Resisting Stem
Material Document And Classification:	Ams5737 Assn Std Single Material Response Mechanical Lock Or Ams5690,type316,cres Assn Std Single Material Response Mechanical Lock
Material Document And Classification:	Astm-a-331 Assn Std Single Material Response Sleeve
Material Document And Classification:	Astm-a-331 Assn Std Single Material Response Stem
Surface Treatment:	Cadmium Mechanical Lock And Passivate Mechanical Lock And Aluminum Mechanical Lock
Surface Treatment:	Cadmium Sleeve And Aluminum Sleeve
Surface Treatment:	Cadmium Stem And Aluminum Stem
Surface Treatment Document And Classification:	Qq-p-416,type1,class3 Fed Spec Single Treatment Response Stem Or Mil-c-83488 Mil Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,type2,class2 Fed Spec Single Treatment Response Mechanical Lock And Qq-p-35 Fed Spec Single Treatment Response Mechanical Lock Or Mil-c-83488 Mil Spec Single Treatment Response Mechanical Lock
Surface Treatment Document And Classification:	Qq-p-416,type2,class2 Fed Spec Single Treatment Response Sleeve Or Mil-c-83488 Mil Spec Single Treatment Response Sleeve

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353S0505D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.