

Description

Fastener part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90353S0509
Minimum Qty (MOQ):	10 EA
NSN:	5320-00-160-2730
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS90353S0509 Specifications

Fastener Length:	0.717 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.333 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.531 Inches Minimum And 0.595 Inches Maximum
Minimum Tensile Strength:	112000 Pounds Per Square Inch
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Hardness Rating:	48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem
Shear Strength:	2340 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment:	Cadmium And Chromate Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353S0509> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.