

Description

Fastener part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS90353S0509 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5320-00-160-2730 |
| Schedule B: | 7318.15.2010 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90353S0509 Specifications

| | |
|---|--|
| Fastener Length: | 0.717 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.162 Inches Minimum And 0.164 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.333 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.531 Inches Minimum And 0.595 Inches Maximum |
| Minimum Tensile Strength: | 112000 Pounds Per Square Inch |
| Hardness Rating: | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem |
| Hardness Rating: | 48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem |
| Shear Strength: | 2340 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment: | Cadmium And Chromate Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve |

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353S0509> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.