

Description

Blind Fastener part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90353S0514
Minimum Qty (MOQ):	10 EA
NSN:	5320-01-108-2563
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS90353S0514 Specifications

Fastener Length:	1.030 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.333 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.844 Inches Minimum And 0.907 Inches Maximum
Hardness Rating:	32.0 Rockwell C Minimum Sleeve And 40.0 Rockwell C Maximum Sleeve
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Shear Strength:	112000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Install With Single Action Tool
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
Material:	Steel Comp 8740 Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,type 1,class 3 Fed Spec Single Treatment Response Stem

How to Order

Order this blind fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353S0514> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.