

P/N MS90353S0602

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS90353S0602

Minimum Qty (MOQ): 15 EA

NSN: 5320-01-055-8828

Schedule B: 8108.90.3060

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N MS90353S0602 Specifications

0.329 Inches Nominal
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.197 Inches Minimum And 0.199 Inches Maximum
Self-plugging Mechanically Locked Stem
0.386 Inches Maximum
Serrated Stem-type W
0.094 Inches Minimum And 0.157 Inches Maximum
48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
100.0 Degrees Nominal
Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
Steel Comp 8740 Stem
66 Fed Std 1st Material Response Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or 66 Fed Std 3rd Material Response
Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve
Mil-s-6049 Mil Spec Single Material Response Stem Or Astm A547 Assn Std Single Material Response Stem
Cadmium Sleeve And Chromate Sleeve
Cadmium Stem
Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this fastener from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/MS90353S0602 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.