

Description

Fastener part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90353S0605D
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-467-7318
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90353S0605D Specifications

Head Style:	Countersunk W/ Reverse Chamfer
Shank Diameter:	0.198 Inches Nominal
Shank Style:	Blind Rivet, Nut And Bolt (assembly)
Expansion Device:	Serrated Stem-type W
End Item Identification:	F-16
Grip Length:	0.490 Inches Nominal
Minimum Tensile Strength:	2100 Pounds Per Square Inch
Hardness Rating:	326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve
Shear Strength:	3450 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 1010 Mechanical Lock
Material:	Steel Sleeve
Material Document And Classification:	Fed-std-66 Fed Std Single Material Response Sleeve
Surface Treatment:	Aluminum Mechanical Lock
Surface Treatment:	Aluminum Sleeve

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353S0605D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.