

Description

MS90353S0607 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90353S0607
Minimum Qty (MOQ):	10
NSN:	5320-01-484-9894
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N MS90353S0607 Specifications

Fastener Length:	0.615 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Head Major Diameter:	0.386 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.406 Inches Minimum And 0.470 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 1010 Mechanical Lock Or Steel Comp 1020 Mechanical Lock Or Steel Comp 1144 Mechanical Lock Or Steel Comp 4037 Mechanical Lock Or Steel Comp 4130 Mechanical Lock
Material Document And Classification:	66 Fed Std All Material Responses Mechanical Lock
Surface Treatment:	Cadmium Mechanical Lock
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Mechanical Lock
Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl2 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416, Ty 1, Cl 3 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353S0607> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.