

P/N MS90353S0608

Description

MS90353S0608 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS90353S0608

Minimum Qty (MOQ):

NSN: 5320-01-058-0822

Schedule B: 7318.15.2010

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









P/N MS90353S0608 Specifications

0.678 Inches Maximum
Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
0.197 Inches Minimum And 0.199 Inches Maximum
Self-plugging Mechanically Locked Stem
0.386 Inches Maximum
Serrated Stem-type W
0.469 Inches Minimum And 0.532 Inches Maximum
32.0 Rockwell C Minimum Sleeve And 40.0 Rockwell C Maximum Sleeve
48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
3450 Single Pounds Per Square Inch
100.0 Degrees Nominal
Installed With Single Action Tool
Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
Steel Comp 8740 Stem
66 Fed Std All Material Responses Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve
Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem
Cadmium Sleeve And Chromate Sleeve
Cadmium Stem
Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/MS90353S0608 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.