

Description

Fastener Length: 1-7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS90353S0620 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-228-5181 |
| Schedule B: | 7318.15.2010 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90353S0620 Specifications

| | |
|--|--|
| Fastener Length: | 1.413 Inches Minimum And 1.443 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.197 Inches Minimum And 0.199 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.376 Inches Minimum And 0.396 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 1.219 Inches Minimum And 1.282 Inches Maximum |
| Minimum Tensile Strength: | 2100 Pounds Per Square Inch |
| Hardness Rating: | 32.0 Rockwell C Minimum Sleeve And 40.0 Rockwell C Maximum Sleeve |
| Hardness Rating: | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem |
| Shear Strength: | 3450 Single Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Locking Ring |
| Material: | Steel Comp 4037 Stem |
| Material: | Steel Comp 4037 Sleeve |
| Material Document And Classification: | Astm A286 Assn Std Single Material Response Locking Ring |
| Material Document And Classification: | Astm A331 Assn Std Single Material Response Stem |
| Material Document And Classification: | Astm A331 Assn Std Single Material Response Sleeve |
| Surface Treatment: | Cadmium Locking Ring And Chromate Locking Ring |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment: | Cadmium Stem |
| Specification/standard Data: | 96906-ms90353 Government Standard And 29666-b100-t Manufacturers Standard |

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353S0620> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.