

Description

Fastener Length: 1-7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90353S0620
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-228-5181
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90353S0620 Specifications

Fastener Length:	1.413 Inches Minimum And 1.443 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.376 Inches Minimum And 0.396 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	1.219 Inches Minimum And 1.282 Inches Maximum
Minimum Tensile Strength:	2100 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Sleeve And 40.0 Rockwell C Maximum Sleeve
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Shear Strength:	3450 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Locking Ring
Material:	Steel Comp 4037 Stem
Material:	Steel Comp 4037 Sleeve
Material Document And Classification:	Astm A286 Assn Std Single Material Response Locking Ring
Material Document And Classification:	Astm A331 Assn Std Single Material Response Stem
Material Document And Classification:	Astm A331 Assn Std Single Material Response Sleeve
Surface Treatment:	Cadmium Locking Ring And Chromate Locking Ring
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Specification/standard Data:	96906-ms90353 Government Standard And 29666-b100-t Manufacturers Standard

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353S0620> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.