

**Description**

blind rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90353U0502
Minimum Qty (MOQ):	10
NSN:	5320-01-204-4779
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N MS90353U0502 Specifications

<b>Fastener Length:</b>	0.280 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.162 Inches Minimum And 0.164 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.333 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.094 Inches Minimum And 0.157 Inches Maximum
<b>Hardness Rating:</b>	326.0 Knoop Minimum Sleeve And 446.0 Knoop Maximum Sleeve
<b>Hardness Rating:</b>	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
<b>Shear Strength:</b>	112000 Single Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Astm A331 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve Or Aluminum Sleeve
<b>Surface Treatment:</b>	Cadmium Stem Or Aluminum Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 1 Cl 3 Fed Spec 1st Treatment Response Stem Or Mil-c-83488 Mil Spec 2nd Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec 1st Treatment Response Sleeve Or Mil-c-83488 Mil Spec 2nd Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353U0502> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.