

Description

blind rivet part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90353U0508
Minimum Qty (MOQ):	10
NSN:	5320-01-311-7160
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS90353U0508 Specifications

Fastener Length:	0.655 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.333 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.469 Inches Minimum And 0.532 Inches Maximum
Minimum Tensile Strength:	112000 Pounds Per Square Inch
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	"u" Denotes Single Action Fasteners Installed With A Single Action Tool
Material:	Steel Comp E4340 Or Steel Comp 4027 Or Steel Comp 4037 Or Steel Comp 4130 Or Steel Comp 4140 Or Steel Comp 4150 Or Steel Comp 4340 Or Steel Comp 4620 Or Steel Comp 4815 Or Steel Comp 6150 Or Steel Comp 8615 Or Steel Comp 8620 Or Steel Comp 8630 Or Steel Comp 8640 Or Steel Comp 8740 Overall
Material Document And Classification:	Astm A331 Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353U0508> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.