

## Description

blind rivet part number

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS90353U0510                                |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5320-01-230-0019                            |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N MS90353U0510 Specifications

|   |  |
|---|--|
| <b>Identification Code Color:</b>                     | Green  |
| <b>Fastener Length:</b>                               | 0.780 Inches Maximum   |
| <b>Head Style:</b>                                    | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>                                | 0.162 Inches Minimum And 0.164 Inches Maximum                                  |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem   |
| <b>Head Major Diameter:</b>                           | 0.333 Inches Nominal   |
| <b>Expansion Device:</b>                              | Serrated Stem-type W   |
| <b>Grip Length:</b>                                   | 0.594 Inches Minimum And 0.657 Inches Maximum                                  |
| <b>Hardness Rating:</b>                               | 326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve                      |
| <b>Hardness Rating:</b>                               | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem                  |
| <b>Shear Strength:</b>                                | 112000 Single Pounds Per Square Inch   |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                 |
| <b>Material:</b>                                      | Steel Overall  |
| <b>Material Document And Classification:</b>          | Astm A331 Assn Std Single Material Response Overall                            |
| <b>Surface Treatment:</b>                             | Cadmium Sleeve And Chromate Sleeve   |
| <b>Surface Treatment:</b>                             | Cadmium Stem   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem                     |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve                   |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353U0510> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.