

Description

Fastener part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90353U0605D
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-343-2796
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90353U0605D Specifications

Fastener Length:	0.490 Inches Nominal
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.386 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.281 Inches Minimum And 0.345 Inches Maximum
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Shear Strength:	112000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Single Action Fastener Installed With A Single Action Tool
Material:	Steel Comp 1010 Mechanical Lock Or Steel Comp 1020 Mechanical Lock Or Steel Comp 1144 Mechanical Lock Or Steel Comp 4037 Mechanical Lock Or Steel Comp 4130 Mechanical Lock
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	66 Fed Std All Material Responses Mechanical Lock
Material Document And Classification:	Astm A331 Assn Std Single Material Response Stem
Material Document And Classification:	Stm A331 Assn Std Single Material Response Sleeve
Surface Treatment:	Aluminum Mechanical Lock
Surface Treatment:	Aluminum Sleeve
Surface Treatment:	Aluminum Stem
Surface Treatment Document And Classification:	Mil-c-83488 Mil Spec Single Treatment Response Mechanical Lock
Surface Treatment Document And Classification:	Mil-c-83488 Mil Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Mil-c-83488 Mil Spec Single Treatment Response Stem

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353U0605D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.