

Description


Self-plugging mechanically locked stem, stainless steel, MS90353 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS90353U0607
Minimum Qty (MOQ):	10
NSN:	5320-01-211-4460
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS90353U0607 Specifications

Fastener Length:	0.616 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.386 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.406 Inches Minimum And 0.470 Inches Maximum
Hardness Rating:	326.0 Knoop Minimum Sleeve And 466.0 Knoop Maximum Sleeve
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Shear Strength:	112000 Single Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Single Action Fastener Installed With A Single Action Tool
Material:	Steel Overall
Material Document And Classification:	Astm A331 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve Or Aluminum Sleeve
Surface Treatment:	Cadmium Stem Or Aluminum Stem
Surface Treatment Document And Classification:	Qq-p-416 Ty 1 Cl 3 Fed Spec 1st Treatment Response Stem Or Mil-c-83488 Mil Spec 2nd Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec 1st Treatment Response Sleeve Or Mil-c-83488 Mil Spec 2nd Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353U0607> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.