

Description

Fastener Length: 1-1/16",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90353U0811
Minimum Qty (MOQ):	5
NSN:	5320-01-197-5358
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS90353U0811 Specifications

Fastener Length:	1.086 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Head Major Diameter:	0.507 Inches Nominal
Expansion Device:	Serrated Stem-type W
Grip Length:	0.656 Inches Minimum And 0.720 Inches Maximum
Hardness Rating:	53.0 Rockwell C Maximum Stem
Countersink Angle:	101.0 Degrees Maximum
Special Features:	Single Action Fastener Installed With A Single Action Tool
Material:	Steel Sleeve
Material:	Steel Stem
Surface Treatment:	Aluminum Sleeve Or Cadmium Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353U0811> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.