

**Description**

Fastener Length: 1-1/16",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS90353U0811
Minimum Qty (MOQ):	5
NSN:	5320-01-197-5358
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N MS90353U0811 Specifications

<b>Fastener Length:</b>	1.086 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.258 Inches Minimum And 0.260 Inches Maximum
<b>Head Major Diameter:</b>	0.507 Inches Nominal
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.656 Inches Minimum And 0.720 Inches Maximum
<b>Hardness Rating:</b>	53.0 Rockwell C Maximum Stem
<b>Countersink Angle:</b>	101.0 Degrees Maximum
<b>Special Features:</b>	Single Action Fastener Installed With A Single Action Tool
<b>Material:</b>	Steel Sleeve
<b>Material:</b>	Steel Stem
<b>Surface Treatment:</b>	Aluminum Sleeve Or Cadmium Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90353U0811> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.