

Description

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS903540503                                 |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5320-00-866-4994                            |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N MS90354-0503 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.342 Inches Nominal  |
| <b>Head Style:</b>                                    | Small Pan   |
| <b>Head Height:</b>                                   | 0.062 Inches Minimum And 0.070 Inches Maximum   |
| <b>Shank Diameter:</b>                                | 0.162 Inches Minimum And 0.164 Inches Maximum   |
| <b>Head Major Diameter:</b>                           | 0.250 Inches Minimum And 0.272 Inches Maximum   |
| <b>Expansion Device:</b>                              | Serrated Stem-type W  |
| <b>Grip Length:</b>                                   | 0.156 Inches Minimum And 0.220 Inches Maximum   |
| <b>Minimum Tensile Strength:</b>                      | 112000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body   |
| <b>Hardness Rating:</b>                               | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem   |
| <b>Material:</b>                                      | Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve  |
| <b>Material:</b>                                      | Steel Comp 8740 Stem  |
| <b>Material Document And Classification:</b>          | 66 Fed Std 1st Material Response Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or 66 Fed Std 3rd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve |
| <b>Material Document And Classification:</b>          | Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem   |
| <b>Surface Treatment:</b>                             | Cadmium Stem Or Cadmium Stem And Chromate Stem  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 1 Cl 3 Fed Spec Single Treatment Response Stem Or Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Stem  |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354-0503> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.