

**Description**

Length: 0.515", Grip: 0.344", protruding head, steel, MS90354 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS903540506
Minimum Qty (MOQ):	10
NSN:	5320-00-985-3787
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS90354-0506 Specifications

<b>Fastener Length:</b>	0.515 Inches Minimum And 0.545 Inches Maximum
<b>Head Style:</b>	Flat/tinner's
<b>Head Height:</b>	0.062 Inches Minimum And 0.070 Inches Maximum
<b>Shank Diameter:</b>	0.162 Inches Minimum And 0.164 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Head Major Diameter:</b>	0.250 Inches Minimum And 0.272 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.344 Inches Minimum And 0.407 Inches Maximum
<b>Material:</b>	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 1 Cl 3 Fed Spec Single Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl @2 Fed Spec Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354-0506> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.