

Description

Length: 0.515", Grip: 0.344", protruding head, steel, MS90354 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS903540506 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-985-3787 |
| Schedule B: | 7318.15.2000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N MS90354-0506 Specifications

| | |
|---|---|
| Fastener Length: | 0.515 Inches Minimum And 0.545 Inches Maximum |
| Head Style: | Flat/tinner's |
| Head Height: | 0.062 Inches Minimum And 0.070 Inches Maximum |
| Shank Diameter: | 0.162 Inches Minimum And 0.164 Inches Maximum |
| Shank Style: | Threaded Self-plugging Shank W/sleeve |
| Head Major Diameter: | 0.250 Inches Minimum And 0.272 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.344 Inches Minimum And 0.407 Inches Maximum |
| Material: | Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 1 Cl 3 Fed Spec Single Treatment Response Stem |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl @2 Fed Spec Single Treatment Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354-0506> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.