

Description

Fastener Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS903540609 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-866-4652 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N MS90354-0609 Specifications

| | |
|---|---|
| Fastener Length: | 0.740 Inches Nominal |
| Head Style: | Small Pan |
| Head Height: | 0.125 Inches Minimum And 0.135 Inches Maximum |
| Shank Diameter: | 0.197 Inches Minimum And 0.199 Inches Maximum |
| Shank Style: | Self-plugging Mechanically Locked Stem |
| Head Major Diameter: | 0.305 Inches Minimum And 0.332 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.531 Inches Minimum And 0.595 Inches Maximum |
| Minimum Tensile Strength: | 112000 Pounds Per Square Inch |
| Hardness Rating: | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem |
| Shear Strength: | 3450 Single Pounds Per Square Inch |
| Material: | Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve |
| Material: | Steel Comp 8740 Stem |
| Material Document And Classification: | 66 Fed Std 1st Material Response Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or 66 Fed Std 3rd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment: | Cadmium Stem |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354-0609> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.