

Description

Fastener Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS903540613
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-075-5201
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS90354-0613 Specifications

Fastener Length:	0.980 Inches Minimum And 1.000 Inches Maximum
Head Style:	Universal
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.305 Inches Minimum And 0.312 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.781 Inches Minimum And 0.845 Inches Maximum
Hardness Rating:	32.0 Rockwell C Minimum Sleeve And 40.0 Rockwell C Maximum Sleeve
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
Material:	Steel Comp 8740 Stem
Material Document And Classification:	66 Fed Std All Material Responses Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve
Material Document And Classification:	Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354-0613> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.