

**Description**

Fastener Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS903540613                                 |
| Minimum Qty (MOQ):      | 5 EA  |
| NSN:                    | 5320-00-075-5201                            |
| Schedule B:             | 7318.15.2010                                |
| ECCN:                   | 9A991                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N MS90354-0613 Specifications

|   |   |
|---|---|
| <b>Fastener Length:</b>                               | 0.980 Inches Minimum And 1.000 Inches Maximum   |
| <b>Head Style:</b>                                    | Universal   |
| <b>Head Height:</b>                                   | 0.125 Inches Minimum And 0.135 Inches Maximum   |
| <b>Shank Diameter:</b>                                | 0.197 Inches Minimum And 0.199 Inches Maximum   |
| <b>Shank Style:</b>                                   | Self-plugging Mechanically Locked Stem  |
| <b>Head Major Diameter:</b>                           | 0.305 Inches Minimum And 0.312 Inches Maximum   |
| <b>Expansion Device:</b>                              | Serrated Stem-type W  |
| <b>Grip Length:</b>                                   | 0.781 Inches Minimum And 0.845 Inches Maximum   |
| <b>Hardness Rating:</b>                               | 32.0 Rockwell C Minimum Sleeve And 40.0 Rockwell C Maximum Sleeve   |
| <b>Material:</b>                                      | Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve  |
| <b>Material:</b>                                      | Steel Comp 8740 Stem  |
| <b>Material Document And Classification:</b>          | 66 Fed Std All Material Responses Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve |
| <b>Material Document And Classification:</b>          | Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem   |
| <b>Surface Treatment:</b>                             | Cadmium Sleeve And Chromate Sleeve  |
| <b>Surface Treatment:</b>                             | Cadmium Stem  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve  |

## How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354-0613> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.