

P/N MS90354-0811

Military-Fasteners.com

## Description

MS90354-0811 Blind Rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

## **Additional Information**

| SKU / Model:            | MS903540811                                 |
|-------------------------|---|
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5320-00-369-4059                            |
| Schedule B:             | 7318.15.2010                                |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



## P/N MS90354-0811 Specifications

| Fastener Length:                                  | 0.906 Inches Maximum   |
|---|--|
| Head Style:                                       | Straight Pan   |
| Head Height:                                      | 0.130 Inches Minimum And 0.140 Inches Maximum  |
| Shank Diameter:                                   | 0.258 Inches Minimum And 0.260 Inches Maximum  |
| Shank Style:                                      | Self-plugging Mechanically Locked Stem   |
| Head Major Diameter:                              | 0.400 Inches Minimum And 0.432 Inches Maximum  |
| Expansion Device:                                 | Serrated Stem-type W   |
| Grip Length:                                      | 0.656 Inches Minimum And 0.720 Inches Maximum  |
| Hardness Rating:                                  | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem  |
| Hardness Rating:                                  | 48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem   |
| Material:   | Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve   |
| Material:   | Steel Comp 8740 Stem   |
| Material:   | Steel Comp 4027 Or Steel Comp 4037 Or Steel Comp 4130 Sleeve   |
| Material Document And<br>Classification:          | 66 Fed Std 1st Material Response Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or 66 Fed Std 3rd Material Response<br>Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve |
| Material Document And<br>Classification:          | Mil-s-6049 Mil Spec Single Material Response Stem Or Astm A547 Assn Std Single Material Response Stem  |
| Material Document And<br>Classification:          | Mil-s-6049 Mil Spec Single Material Response Or Astm A547 Assn Std Single Material Response Stem   |
| Material Document And<br>Classification:          | 66 Fed Std 1st Material Response Or Astm A547 Assn Std 2nd Material Response Or 66 Fed Std 3rd Material Response Or Mil-s-6758 Mil<br>Spec 3rd Material Response Sleeve                      |
| Surface Treatment:                                | Cadmium Sleeve And Chromate Sleeve   |
| Surface Treatment:                                | Cadmium Stem   |
| Surface Treatment:                                | Cadmium And Chromate Sleeve  |
| Surface Treatment Document And<br>Classification: | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem   |
| Surface Treatment Document And<br>Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve   |

## How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/MS90354-0811</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.