

**Description**

Fastener Length: 1

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS903540813
Minimum Qty (MOQ):	5
NSN:	5320-00-877-7317
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS90354-0813 Specifications

<b>Fastener Length:</b>	1.031 Inches Nominal
<b>Head Style:</b>	Small Pan
<b>Head Height:</b>	0.130 Inches Minimum And 0.140 Inches Maximum
<b>Shank Diameter:</b>	0.258 Inches Minimum And 0.260 Inches Maximum
<b>Shank Style:</b>	Self-plugging Mechanically Locked Stem
<b>Head Major Diameter:</b>	0.400 Inches Minimum And 0.432 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.781 Inches Minimum And 0.845 Inches Maximum
<b>Minimum Tensile Strength:</b>	112000 Pounds Per Square Inch
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body
<b>Hardness Rating:</b>	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
<b>Material:</b>	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty,cl 3 Fed Spec Single Treatment Response Stem

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354-0813> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.