

P/N MS90354-0815

Military-Fasteners.com

Description

Fastener Length: 1-5/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS903540815
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-814-2611
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N MS90354-0815 Specifications

1.141 Inches Minimum And 1.171 Inches Maximum
Straight Pan
0.130 Inches Minimum And 0.140 Inches Maximum
0.258 Inches Minimum And 0.260 Inches Maximum
Self-plugging Mechanically Locked Stem
0.400 Inches Minimum And 0.432 Inches Maximum
Serrated Stem-type W
0.906 Inches Minimum And 0.970 Inches Maximum
32.0 Rockwell C Minimum Sleeve And 40.0 Rockwell C Maximum Sleeve
48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
5900 Single Pounds Per Square Inch
Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
Steel Comp 8740 Stem
66 Fed Std All Material Responses Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve
Astm A547 Assn Std Single Material Response Stem Or Mil-s-6049 Mil Spec Single Material Response Stem
Cadmium Sleeve And Chromate Sleeve
Cadmium Stem
Qq-p-416,ty 1 Cl 3 Fed Spec Single Treatment Response Stem
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

How to Order

Order this fastener from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/MS90354-0815</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.