

P/N MS90354-0818

Description

Fastener Length: 1-3/8"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS903540818

Minimum Qty (MOQ): 1 EA

NSN: 5320-00-093-7453

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N MS90354-0818 Specifications

Fastener Length:	1.344 Inches Nominal
Head Style:	Undercut Pan No. 2
Head Height:	0.130 Inches Minimum And 0.140 Inches Maximum
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.400 Inches Minimum And 0.432 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	1.094 Inches Minimum And 1.157 Inches Maximum
Hardness Rating:	32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Material:	Steel Comp 1010 Mechanical Lock Or Steel Comp 1020 Mechanical Lock Or Steel Comp 1144 Mechanical Lock Or Steel Comp 4037 Mechanical Lock Or Steel Comp 4130 Mechanical Lock Or Iron Alloy 660 Mechanical Lock
Material:	Steel Comp 4027 Body Or Steel Comp 4037 Body Or Steel Comp 4130 Body
Material:	Steel Comp 8740 Stem
Material Document And Classification:	66 Fed Std 1st Material Response Body Or Astm A547 Assn Std 2nd Material Response Body Or Mil-s-6758 Mil Spec 3rd Material Response Body
Surface Treatment:	Cadmium Body And Chromate Body
Surface Treatment:	Cadmium Mechanical Lock Or Passivate Mechanical Lock
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Fed Spec 1st Treatment Response Mechanical Lock Or Qq-p-35 Fed Spec 2nd Treatment Response Mechanical Lock
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Body

How to Order

Order this fastener from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/MS90354-0818 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/MS90354-0818 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/MS90354-0818 and selecting the quantity you want then click "add to cart".