

## P/N MS90354-0818

### **Description**

Fastener Length: 1-3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS903540818

Minimum Qty (MOQ): 1 EA

NSN: 5320-00-093-7453

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS90354-0818 Specifications

| Fastener Length:                                  | 1.344 Inches Nominal  |
|---|---|
| Head Style:                                       | Undercut Pan No. 2  |
| Head Height:                                      | 0.130 Inches Minimum And 0.140 Inches Maximum   |
| Shank Diameter:                                   | 0.258 Inches Minimum And 0.260 Inches Maximum   |
| Shank Style:                                      | Self-plugging Mechanically Locked Stem  |
| Head Major Diameter:                              | 0.400 Inches Minimum And 0.432 Inches Maximum   |
| Expansion Device:                                 | Serrated Stem-type W  |
| Grip Length:                                      | 1.094 Inches Minimum And 1.157 Inches Maximum   |
| Hardness Rating:                                  | 32.0 Rockwell C Minimum Body And 40.0 Rockwell C Maximum Body   |
| Hardness Rating:                                  | 48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem   |
| Material:   | Steel Comp 1010 Mechanical Lock Or Steel Comp 1020 Mechanical Lock Or Steel Comp 1144 Mechanical Lock Or Steel Comp 4037 Mechanical Lock Or Steel Comp 4130 Mechanical Lock Or Iron Alloy 660 Mechanical Lock |
| Material:   | Steel Comp 4027 Body Or Steel Comp 4037 Body Or Steel Comp 4130 Body  |
| Material:   | Steel Comp 8740 Stem  |
| Material Document And Classification:             | 66 Fed Std 1st Material Response Body Or Astm A547 Assn Std 2nd Material Response Body Or Mil-s-6758 Mil Spec 3rd Material Response Body  |
| Surface Treatment:                                | Cadmium Body And Chromate Body  |
| Surface Treatment:                                | Cadmium Mechanical Lock Or Passivate Mechanical Lock  |
| Surface Treatment:                                | Cadmium Stem  |
| Surface Treatment Document And Classification:    | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem  |
| Surface Treatment Document And Classification:    | Qq-p-416,ty 2 Fed Spec 1st Treatment Response Mechanical Lock Or Qq-p-35 Fed Spec 2nd Treatment Response Mechanical Lock  |
| Surface Treatment Document And Classification:    | Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Body  |
| Classification:<br>Surface Treatment Document And |   |

## **How to Order**

Order this fastener from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/MS90354-0818">https://military-fasteners.com/rivets/blind+rivets/MS90354-0818</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.