

## Description

Fastener Length: 45/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS903541007
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-192-0658
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N MS90354-1007 Specifications

<b>Fastener Length:</b>	0.678 Inches Minimum And 0.708 Inches Maximum
<b>Head Style:</b>	Undercut Pan No. 2
<b>Head Height:</b>	0.131 Inches Minimum And 0.141 Inches Maximum
<b>Shank Diameter:</b>	0.310 Inches Minimum And 0.312 Inches Maximum
<b>Head Major Diameter:</b>	0.480 Inches Minimum And 0.522 Inches Maximum
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Grip Length:</b>	0.406 Inches Minimum And 0.460 Inches Maximum
<b>Hardness Rating:</b>	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
<b>Shear Strength:</b>	8500 Single Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
<b>Material:</b>	Steel Comp 8740 Stem
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or Mil-s-6049 Mil Spec 3rd Material Response Sleeve
<b>Surface Treatment:</b>	Cadmium Sleeve And Chromate Sleeve
<b>Surface Treatment:</b>	Cadmium Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve

## How to Order

Order this fastener from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/MS90354-1007> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.