

P/N MS90354S0504

Description

MS90354S0504 Blind Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS90354S0504

Minimum Qty (MOQ):

NSN: 5320-00-164-0852

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



^{*} See page 2 for technical characteristics

P/N MS90354S0504 Specifications

Fastener Length:	0.405 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.062 Inches Minimum And 0.070 Inches Maximum
Shank Diameter:	0.162 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Self-plugging Mechanically Locked Stem
Head Major Diameter:	0.250 Inches Minimum And 0.272 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.219 Inches Minimum And 0.282 Inches Maximum
Minimum Tensile Strength:	112000 Pounds Per Square Inch
Hardness Rating:	48.0 Rockwell C Minimum Stem And 53.0 Rockwell C Maximum Stem
Hardness Rating:	48.0 Rockwell C Minimum And 53.0 Rockwell C Maximum Stem
Shear Strength:	2340 Single Pounds Per Square Inch
Material:	Steel Comp 4027 Sleeve Or Steel Comp 4037 Sleeve Or Steel Comp 4130 Sleeve
Material:	Steel Comp 8740 Stem
Material:	Steel Comp 4027 Or Steel Comp 4037 Or Steel Comp 4130 Sleeve
Material Document And Classification:	66 Fed Std 1st Material Response Sleeve Or Astm A547 Assn Std 2nd Material Response Sleeve Or 66 Fed Std 3rd Material Response Sleeve Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Stem Or Astm A547 Assn Std Single Material Response Stem
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Or Astm A547 Assn Std Single Material Response Stem
Material Document And Classification:	66 Fed Std 1st Material Response Or Astm A547 Assn Std 2nd Material Response Or 66 Fed Std 3rd Material Response Or Mil-s-6758 Mil Spec 3rd Material Response Sleeve
Surface Treatment:	Cadmium Sleeve And Chromate Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment:	Cadmium And Chromate Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Stem

How to Order

